

Gloves Ansell, Easy tear glove, nitrile coating


Produktnummer: ANS11-812

Ultra-thin light-duty gloves designed to preemptively tear if entangled in rotating tools

Specialized protection: Designed for the operation of rotating machinery, HyFlex 11-812 industrial gloves' ultrathin liner deliberately tears when they become entangled and the wearer is at risk of severe injury

Advanced comfort and dexterity: Developed with ERGOFORM Technology and ZONZ Comfort Fit knitwork, these HyFlex gloves offer users a tailored fit, for less strain and tension and greater comfort and dexterity

Heightened tactility: Their thin liner also enhances tactile sensitivity, making them ideal for delicate handling





- This glove will not directly protect the worker from injuries caused by contact with a sharp or high-speed rotating machine.
- If a glove becomes entangled in a rotating machine, whether or not it tears, it should be discarded and not used again.
- HyFlex 11-812 industrial gloves have been designed for rotating tools with a minimum torque of 10 Nm [7.4 ft-lb], reaching speeds of over 200 rotations per minute (RPM). HyFlex 11-812 safety gloves are not recommended for rotating tools with lower torque and/or speed levels. An in-depth analysis of application requirements, using AnsellGUARDIAN, is essential before use.









Les mer om produktet her:

https://www.redwingnordic.com/product?number=ANS11-812

Utskriftsdato: 01.11.2025