



# Tether Ring™, Medium Max load 1kg/2,2lbs

Produktnummer: NLG101273

Tether Ring™ Medium – creates a tether point on tools with captive holes. Easy-to-use, available in multiple sizes for any tool.

- NLG Tether Rings™ are an economical solution for creating a tether point on a tool with a captive hole. Shaped tools, such as spanners, are also particularly suited to this type of attachment as the Tether Rings™ move freely along the length of the tool and allow the tool to rotate through 360 degrees.
- Quick and simple to apply, the NLG Tether Ring™ only requires a pair of pliers to open and wind onto the tool similar to a key ring.
- The NLG Tether Rings™ are specially coated to prevent corrosion and provide a dependable tether point for the harshest working environments.
- Max Load: 1 KG / 2.2 LBS
- Safety Standards: ANSI/ISEA 121-2023, CE / UKCA, NS 9611:2022+AC
- Load Tested and Third-party Certified: Dynamic (2:1 Safety Factor)
- NLG ID™ Technology / Scannable Compatible
- Unique Serial Number
- Dimensions: 25mm (Diameter)
- Max Lanyard Length: 200 CM / 78 IN



**Manufacturer website:** [NLG - Tether Ring](#)

## Standarder

Standarder

ANSI/ISEA 121-2023, NS 9611:2022+AC





Les mer om produktet her:

<https://www.redwingnordic.com/product?number=NLG101273>