



Tether Tape™ Self-fusing Silicone

Produktnummer: NLG101355

Tether Tape™ — self-fusing silicone creates a load-rated tether point in seconds. No adhesive residue, instant tool preparation


- NLG Tether Tape™ uses advanced self-fusing silicone technology to create load-rated tether points on any tool within seconds. As most tools are not designed with a manufactured attachment point, NLG's Instant Tether System™ uses Tether Tape™ and D Rings to quickly retrofit tether points, ready for any tool lanyard to connect to.
- No heat source or other specialist tools are required to fit Tether Tape™ as it is simply activated by stretching. It fully bonds to itself within 24 hours at room temperature but is tested and certified for immediate use. Because no adhesive is used in the process, the retrofitted tool tether can be easily removed when no longer required, leaving no sticky residue or permanent damage to the tool.
- NLG Tether Tape™ features a fibreglass reinforcement mesh for exceptional strength, durability and resistance against tears and punctures.
- Pair with a Large D Ring, Small D Ring or Non-Conductive D Ring for common hand tools or use with Tether Choke™ single arm or twin arm when securing power tools and large straight shafted tools. Based on a general selection of hand tools, one roll will tether up to 10 tools on average.
- Reduce wastage when the tether point is no longer needed by simply cutting away the Tether Tape™ and retaining the D Ring Tether or Choke™ so that it can be reused on another tool.
- The flexibility and speed of the combined Instant Tether System™ make Tether Tape™ the first choice across a broad range of industries. Keep a roll to hand, and a selection of D Rings, and you'll never be caught out again.



Standarder

Standarder

ANSI/ISEA 121-2023, NS 9611:2022+AC





Les mer om produktet her:

<https://www.redwingnordic.com/product?number=NLG101355>